

ecoANCHOR

The ecoAnchor has been designed to provide a temporary anchor for your safety when working at height. The anchor is a totally unique concept in fall protection and uses renewable resources for both manufacture and installed use.

The ecoAnchor is a dead weight water bladder and is compatible for a large variety of roof surfaces including composites and mineral felts and can be used on roofes with up to 15° pitches.

The anchor has been independently tested and exceeds the European EN795 Class E standards.

KEY FEATURES

- Easy to use, just roll out and fill with water (must be at least 2.5m from an edge)
- Stop filling when the release vent engages
- Weighs 8kg when empty
- Fire resistant neoprene R re-enforced with Nylon material.
- Puncture resistant
- Suitable for Concrete, Tarmac, Felt and Mineral roof surfaces
- Built in attachment point
- Simply empty the bladder when the job is finished



Code **ECO**

MATERIALS & CONSTRUCTION

- Fire resistant Neoprene R re-enforced Nylon
- Pressure loading 2.7kN/m²
- Puncture resistant meets FED STD 191 Part 1520
- Dimensions 1.45m x 1.45m x 0.2m
- Weight when full 430kg
- Canvas bag

TESTING & QUALITY CONTROL

- CE marked and certified to EN795 Class E
- Conforms to AS/NZS 1891
- 12 month inspection and servicing requirements in accordance with manufacturer's instructions and AS/NZS 1891.3
- Saferight is an ISO 9001 Certified Company

SAFE WORKING LOAD (SWL) 140kg - maximum operator weight including tools.

For full product details and quotes go to saferight.com.au Or contact your nearest Saferight office

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au

SAFERIGHT TRAINING ACADEMY

33 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1000 Fax: +61 08 9477 6946
training@saferight.com.au

www.saferight.com.au