

ANCHOR SLINGS

Anchor Slings are designed to provide a temporary anchor point to a suitably rated structure such as steel work.

Saferight's range of Anchor Slings are perfect for the job.

KEY FEATURES

- Simple to use temporary anchor point
- Easy, secure connection to the steel D loops

Code **SD**

MATERIALS & CONSTRUCTION

- 25mm Supertape Webbing
- Mild Steel D loops

TESTING & QUALITY CONTROL

- 100% visual inspection
- Saferight is an ISO 9001 Certified Company
- 24kN strength

OPTIONS

CODE	LENGTH	DESCRIPTION
S60D	0.6m	SD Anchor Sling 60cm
S100D	1.0m	SD Anchor Sling 100cm
S500D	5.0m	SD Anchor Sling 500cm



SAFE WORKING LOAD (SWL) Maximum 2400kg (24kN).

For full product details and quotes go to saferight.com.au Or contact your nearest Saferight office

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au

SAFERIGHT TRAINING ACADEMY

33 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1000 Fax: +61 08 9477 6946
training@saferight.com.au

www.saferight.com.au