

FALL ARREST LANYARDS

Lanyards are designed to be a link between and attachment anchor point and a harness providing the user with maximum safety. They are manufactured to limit the amount of force transferred to the body in the event of a fall to 6kN.

Saferight manufactures a wide range of shock absorbing lanyards which are suitable for use in all situations.

KEY FEATURES

- limits load to 6kN in the event of a fall

Code L

MATERIALS & CONSTRUCTION

- Shock Absorber
- 25mm Supertape webbing
- Alloy, mild steel or stainless steel connectors
- All models are less than 1kg in weight

TESTING & QUALITY CONTROL

- All lanyards meet the requirements of AS/NZS 1891.1
- 100% visual inspection
- Saferight is an ISO 9001 Certified Company

OPTIONS

with Snap Hooks

Specifications: Fall arrest lanyard with double action snap hooks at both ends

Application: Working at heights and confined spaces where there is potential to fall

Code	L12K5	1.2m
	L15K5	1.5m
	L2K5	2m



SAFE WORKING LOAD (SWL)

Maximum operator weight including tools shall be no more than 140kg.

For full product details and quotes go to saferight.com.au Or contact your nearest Saferight office

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au

6277, 100, 0
6.7, 1
06666:00:0
70
ENL00VF00

www.saferight.com.au

000/50

FALL ARREST LANYARDS

with Triple Action Karabiners

Specifications: Fall arrest lanyard with triple action karabiners at both ends

Application: Working at heights and confined spaces where there is potential to fall

Code	L12K1	1.2m
	L15K1	1.5m
	L2K1	2m



with Shark Hook and Snap Hook

Specifications: Fall arrest lanyard with double action snap hook at one end and double action shark hook at the other end

Application: Working at heights and confined spaces where there is potential to fall

Code	L12K59	1.2m
	L15K59	1.5m
	L2K59	2m



with Shark Hook and Karabiner

Specifications: Fall arrest lanyard with triple action karabiner at one end and double action shark hook at the other end

Application: Working at heights and confined spaces where there is potential to fall

Code	L12K19	1.2m
	L15K19	1.5m
	L2K19	2m



SAFE WORKING LOAD (SWL)

Maximum operator weight including tools shall be no more than 140kg.

For full product details and quotes go to saferight.com.au Or contact your nearest Saferight office

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au

SAFERIGHT TRAINING ACADEMY - HIGH RISK TRAINING

107 Radium Street, Welshpool, WA 6106 Tel:
+61 08 9334 1000
bookings@saferight.com.au

www.saferight.com.au