

NYLON ROPE LANYARDS

Lanyards are designed to be a link between an attachment anchor point and a harness providing the user with maximum safety. They are manufactured to limit the amount of force transferred to the body to 6kN in the event of a fall.

Saferight manufactures a wide range of shock absorbing lanyards which are suitable for use in most situations. Lanyards can be customised to your individual requirements.

KEY FEATURES

- In the event of a fall, loads on the body are reduced to 6kN
- Fixed length (non adjustable)
- All models weigh less than 1kg
- Inbuilt Energy Absorber

Code **LNRK5**

APPLICATION

- Working at heights

with Triple Action Karabiners

Specifications: Nylon rope with triple action karabiner at both ends

Application: Working at heights

Code	LNR12K1	1.2m
	LNR16K1	1.6m
	LNR2K1	2.0m

TESTING & QUALITY CONTROL

- All lanyards meet the requirements of AS/NZS 1891.1:2007
- 100% Visual inspection
- Saferight is an ISO 9001 Certified Company

MATERIALS & CONSTRUCTION

- 12mm Nylon Rope
- Triple Action Carbon Steel Nickel Plated Karabiner (K1)
- Double Action Aluminium Alloy Snap Hook (K5)



with Triple Action Karabiners

Specifications: Nylon rope with double action snap hooks at both ends

Application: Working at heights

Code	LNR12K5	1.2m
	LNR16K5	1.6m
	LNR2K5	2.0m



SAFE WORKING LOAD (SWL) Maximum combined weight including tools shall be no more than 140kg
For full product details and quotes go to saferight.com.au Or contact your nearest Saferight office

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au

SAFERIGHT TRAINING ACADEMY - HIGH RISK TRAINING

107 Radium Street, Welshpool, WA 6106
Tel: +61 08 9334 1000
bookings@saferight.com.au

www.saferight.com.au

LNR Datasheet Rev 2 08.07.21