

NYLON ROPE LANYARDS

Lanyards are designed to be a link between and attachment anchor point and a harness providing the user with maximum safety. They are manufactured to limit the amount of force transferred to the body in the event of a fall to 6kN.

Saferight manufactures a wide range of shock absorbing lanyards which are suitable for use in all situations.



APPLICATION

- Working at heights

KEY FEATURES

- In the event of a fall, loads on the body are reduced to 6kN
- Fixed length (non adjustable)
- All models weigh less than 1kg

Code **LNRK5**

MATERIALS & CONSTRUCTION

- 12mm Nylon Rope
- Forged Aluminium Alloy Snap Hooks (K5) at both ends

TESTING & QUALITY CONTROL

- All lanyards meet the requirements of AS/ NZS 1891.1:2007
- 100% Visual inspection
- Saferight is an ISO 9001 Certified Company

OPTIONS

CODE	LENGTH	DESCRIPTION
LNR12K5	1.2m	1.2m Fixed Nylon Rope with K5's
LNR16K5	1.6m	1.6m Fixed Nylon Rope with K5's
LNR2K5	2.0m	2.0m Fixed Nylon Rope with K5's

SAFE WORKING LOAD (SWL) Maximum combined weight including tools shall be no more than 140kg

For full product details and quotes go to saferight.com.au Or contact your nearest Saferight office

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, BELMONT, WA 6104
PO Box 176, BELMONT, WA 6984
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au

SAFERIGHT TRAINING ACADEMY - HIGH RISK TRAINING

107 Radium Street, Welshpool, WA 6106
Tel: +61 08 9334 1000
bookings@saferight.com.au

www.saferight.com.au

LNR K5 Datasheet Rev 2 08.07.21