

IKAR RETRACTING LANYARD

Retracting lanyards are ideal for many fall arrest applications where the anchor point is within 2.5m of your exposed edge or there is a need to reduce fall distances.

This aluminium housed fall arrest block is a sturdy, low maintenance device fitted with internal energy absorption which allows the equipment to last longer even in harsh weather conditions.

IKAR Retracting Lanyard series sold by Saferight are Australian Standard AS/NZS1891.3:1997 certified and is UV Degradation tested to 12kN.

It acts as an inertia device, similar to a seat belt, and locks immediately in the event of a fall, reducing both fall distance and forces.

IKAR fall arrest blocks are renowned worldwide for their robust design and engineering excellence. Its ideal application is where the anchor point is overhead, however it has been tested and rated for 360° range of use (can be anchored at any point of 360°).

The working load limit is up to 136kg person for each unit.

KEY FEATURES

- Twin IKAR's on a single Karabiner
- Tested & certified to AS/NZS 1891.3 (BMP No. 718260)
- UV Degradation is tested to 12kN
- In the event of a free fall, the Lanyard locks off immediately reducing distances and fall forces
- Internal energy absorber designed within the housing, ensuring user protection even when the webbing is fully extended. This also aides in reducing the over all size of the device and reduces the exposure of external materials to the environment.

MATERIALS & CONSTRUCTION

- 25mm blue super tape webbing
- Heavy duty aluminium housing
- Triple Action Carbon Steel Nickel Plated Karabiners
- Weight 2.4kg

APPLICATIONS

- Working at heights
- Limited free fall
- Perfect for the mining/construction industry

CODE: RLIKARDB2



**UV TESTED
TO 12kN**

For full product details and quotes, email saleswa@saferight.com.au OR contact our Saferight office.

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, Belmont, WA 6104
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au



Quality
ISO 9001
Licence: QEC20205
SAI GLOBAL



IKAR RETRACTING LANYARD

UV TESTED
TO 12kN

TESTING & QUALITY CONTROL

- Tested & certified to AS/NZS 1891.3:1997 (BMP No. 718260)
- 6 month servicing requirements in accordance with AS/NZS 1891.4:2009
- 100% inspected
- Saferight is an ISO 9001 Certified Company
- Safety factor of 2: Load bearing web of the fly end of the webbing is UV tested to ensure a guaranteed strength of 12 kN is maintained at the end of the 10 year life of the product (eg 2 x 6 Kn = 12 kN SWL for a 136kg user)
- Complies with AS/NZs 1891.1:2007 for UV compliance by an independent NATA test laboratory

TRAINING & INSPECTION

- In accordance with AS/NZS 1891.4:2009, all users of height safety equipment must have been trained in its safe use.
- Saferight offers a range of Nationally Recognised Height Safety, Confined Spaces and Rescue Courses.
- Items should always be visually inspected before and after each use, and undergo inspection by a competent person every 6 months in accordance with AS/NZS 1891.4:2009
- Saferight offers a full inspection service for all Height Safety, Confined Spaces and Rescue equipment.



For full product details and quotes, email saleswa@saferight.com.au OR contact our Saferight office.

TOLL FREE: 1800 352 335

PERTH WA - HEAD OFFICE

42 Belmont Avenue, Belmont, WA 6104
Tel: +61 08 9334 1010 Fax: +61 08 9334 1001
saleswa@saferight.com.au



Quality
ISO 9001
Licence: QEC20205
SAI GLOBAL

